

Compression control during hierarchical image compression

M.V. Gashnikov¹, N.I. Glumov¹, V.V. Sergeev¹

¹ *Samara State Aerospace University*

Abstract

A new method of ensuring a given compression ratio for hierarchical image compression is proposed. The main idea of the method is to use different values of the control parameter (maximum error) for various scale levels of image representation and to correct the error value at the last level, depending on the amount of compressed data obtained.

Keywords: compression control, image compression, compressed data, error.

Citation: Gashnikov MV, Glumov NI, Sergeev VV. Compression control during hierarchical image compression. *Computer Optics* 2004; 26: 110-112.

[Access full text \(in Russian\)](#)

References

- [1] Aleksandrov VV, Gorsky ND. Image representation and processing: a recursive approach [In Russian]. Leningrad: "Nauka" Publisher; 1985.
- [2] Soifer VA, ed. Methods of computer image processing. Moscow: "Fizmatlit" Publisher; 2001.
- [3] Gashnikov MV, Glumov NI, Sergeev VV. The method of image compression in operational remote sensing systems [In Russian]. Proceedings of the IX All-Russian Conference "Mathematical methods of pattern recognition" (MMRO-9-99); 160-163.
- [4] Gashnikov MV, Glumov NI, Sergeev VV. Information technology of image compression for real-time systems [In Russian]. Proceedings of the VI International Conference "Pattern Recognition and Image Analysis" (ROAI-6-2002) 2002; 1: 138-141.
- [5] Kolesnik VD, Poltyrev GS. Course of information theory [In Russian]. Moscow: "Nauka" Publisher; 1982.
- [6] Kortman CM. Redundancy reduction – a practical method of data compression. *Proc IEEE* 1967; 55(3): 253-263.